



eDIN 4813 DMX/RDM Installation Splitter

RDM-enabled opto-splitters for permanent installations, mounted in NEMA-1 enclosures, complete with conduit knockouts and terminal strip connections for fast, easy installation.

FEATURES

- Modules are mounted and pre-wired; the whole box is ready to install
- Up to 3 eDIN 1009 DMX/RDM opto-splitters - up to 12 outputs total
- Up to 3 inputs, or daisy-chain one source
- Removable terminal strip connectors
- No fuses, self resetting data links
- Fully supports the E1.20 Remote Device Management (RDM) talkback extension to DMX512 on all ports, including the pass thru
- 2500V opto-isolation input to output
- 250V fault protection on all DMX ports
- Wide range power supply
- Power, DMX present and transmit indicators
- ETL Listed

MODEL DESCRIPTION

4813	4 way DMX/RDM Installation Splitter
4814	8 way DMX/RDM Installation Splitter
4815	12 way eDIN Installation Repeater

SPECIFICATIONS

Power Supply	UL listed, DIN rail mountable, wide range input 100-240VAC, 50/60 Hz
Isolation	<ul style="list-style-type: none"> • 2500V opto-isolation input to output • 250V fault protection
Size	
4813	10.25" x 13.25" (260mm x 335mm)
4814 & 4815	10.25" x 23.25" (260mm x 590mm)

